

Transfer speed 10Gbps “Dual USB3”

Under development

Dual USB3 Camera DDU Series

New **DDU2607MG** 26.2 MP 28.4 fps B/W

New **DDU2607MCG** 26.2 MP 28.4 fps Color

New **DDU2607MCF** 26.2 MP 28.4 fps Color



Features

- 1: Transfer speed 10Gbps with USB 5Gbps (USB3.1 Gen1) 2 ports
- 2: Toshiba Teli original interface “Dual USB3”
- 3: Convenient control with our software development kit “TeliCamSDK”
- 4: Available with Single USB

Main Specifications

Model	New DDU2607M Series	DDU1607M Series	DDU1207M Series
Imager	Gpixel GMAX0505	onsemi XGS16000	Sony IMX253
Resolution	26.2 MP (5,120 x 5,120 pix)	16 MP (4,000 x 4,000 pix)	12.3 MP (4,096 x 3,000 pix)
Pixel size	2.5 x 2.5 μm	2.74 x 2.74 μm	3.45 x 3.45 μm
Image size	1.1 type	1.1 type	1.1 type
Frame rate	28.4 fps (Dual) 14 fps (Single)	47 fps (Dual) 23 fps (Single)	62 fps (Dual) 31 fps (Single)
Interface	USB 5Gbps (USB3.1 Gen1) x 2 channel		

* USB3 Vision is trademark or registered trademark of AIA (Automated Imaging Association).

* The company names, product names, and standard names listed might be trademarks or registered trademarks of each company or organization.

Toshiba Teli Corporation